



SERIE 9 M	MECHANICAL DIFFERENTIALS	
DIESEL ENGINE	FPT NEF 151 kW (205 hp), 6-cylinder, Common Rail Turbo intercooler, STAGE V, AdBlue	
DRIVE SYSTEM	Hydrostatic 4-wheel drive with mechanical differentials	
SPRAY TANK CAPACITY	3500 Litres or 4000 Litres	
RINSING TANK CAPACITY	300 L	
SUSPENSIONS	Front and rear active pneumatic with air compressor + hydraulic suspension system, pneumatic on boom parallelogram	
BRAKES	PARKING BRAKE: Electric negative brake / SERVICE BRAKE: On the front and rear axles	
GEAR BOX	Electro-hydraulic with 4 speeds (Max 40 km/h)	
STEERING SYSTEM	4 steering wheels with 4 steering modes	
CAB	Cat. 4, pressurized, air conditioned, heated, 2 activated carbon filters and pneumatic driver's seat	
COMPUTER	ARAG orTRIMBLE, with or without GPS	
CLEARANCE	650 - 750 mm	
BOOM	24 - 27 - 28 - 30 m Steel/Aluminium (optional air assisted kit)	
DIMENSIONS		Length: 7800 mm Width: 2550 mm (2700 mm aluminium) Height: 3700 mm Wheel base: 3150 mm
TARE	7800 - 8100 kg	
TYRES	320, 340, 380, 420, 480, 540, 600, 710	