



SERIE GT	TECHNICAL FEATURES	
DIESEL ENGINE	FPT NEF 4500 cc, 125 kw (170 hp), 4-cylinder, Turbo intercooler, STAGE V, AdBlue JOHN DEERE 6800 cc, 138 kw (185 hp), Turbo intercooler, Common Rail, 6-cylinder, TIER 3A (for non-EU Countries)	
DRIVE SYSTEM	N°2 Hydrostatic pumps, 4-wheel drive, Poclain hydraulic motors	
SPRAY TANK CAPACITY	3500 + 5% (1750 + 1750) in stainless steel	
SUSPENSIONS	Hydraulic air suspensions on the front wheels and air suspension on the boom lift guid	
BRAKES	PARKING BRAKE: Passive, at the rear wheels SERVICE BRAKE: Disk brakes	
GEAR BOX	Electro-hydraulic with 2 speeds (0-18 km/h, 0-39 km/h)	
STEERING SYSTEM	4 steering wheels with 4 steering modes	
CAB	Class IV, pressurized, air conditioned, heated, n°2 activated carbon filters and pneumatic driver's seat	
COMPUTER	ARAG or TRIMBLE, with or without GPS	
CLEARENCE	2850mm under the machine chassis, 1100mm under the central section	
BOOM	18 - 21 - 24 m, horizontal folding system, with or without air assisted kit.Boom water sections: 5 - 7 - 9	
DIMENSIONS		Length 6670 mm Width 2550 mm Height 3700 mm Weel base 2870 mm Tare 9200 kg
TYRES	300, 320, 340	